

Atlantic

Chemical Company

Biodegradable

Breakaway Mop/Strip Finish Reliquifier

This floor stripper was formulated to quickly remove heavy floor finish build-up, especially those hardened by high-speed burnishing and urethane fortification. The powerful balance of solvents and amines instantly penetrates through heavy build-ups and attacks the polymer cross-linking for easy removal. Completely evaporates leaving no trace of alkali residue which eliminates excessive rinsing and neutralizing.

DIRECTIONS FOR USE

- Dilute stripper as needed with COOL water. Hot water will cause the solvents to evaporate rapidly reducing its effectiveness.
Normal Buildup: Mix 1 part stripper to 6 parts cool water (21 ounces per gallon).
Heavy Buildup: Mix 1 part stripper to 4 parts cool water (32 ounces per gallon).
- Apply solution liberally to floor with a clean mop and allow to stand for 5 minutes. Do Not Allow Solution To Dry On Floor.
- Agitate solution with floor machine and stripping pad if necessary. Pick up remaining solution with a wet vacuum or automatic scrubber.
- Rinse floor with clean water if necessary. Allow to dry thoroughly before applying sealer or finish.

Technical Data

Color	Green
Odor	Sassafrass Scented
Clarity	Clear
Sediment	None
pH @25 °C	11.5-12.0
Nonvolatile Solids	1.0-1.5%
Viscosity @25 °C	Free Flowing
Specific Gravity @20 °C	0.997
Weight Per Gallon @20 °C	8.22 lbs
Phosphates	None

WARNING: POISON
SEVERE SKIN AND EYE IRRITANT
KEEP OUT OF REACH OF CHILDREN

Effects of Over Exposure: May cause severe skin and eye irritation. If ingested, may cause burns to mouth, throat and gastrointestinal system. Inhalation may cause irritation to nasal membranes with headache and sinus pain. Consult product label for emergency and first aid procedures.

Distributed nationally by

GENERAL DISTRIBUTING COMPANY, INC.

11433-F Cronridge Drive • Owings Mills, MD 21117

Phone: 800.655.2187 • Fax: 877.654.8165 • www.GeneralDistCo.com • Customer.Support@GeneralDistCo.com