



Micro Shield Floor Care

The Products...

Breakaway Mop/Strip Finish Reliquifier

A new product formulated to quickly penetrate and dissolve the most difficult-to-remove floor finishes hardened by high-speed burnishing and urethane fortification. Dramatically reduces the amount of time and labor expended with the use of conventional floor strippers. Biodegradable and non-corrosive.

Neutralizer & Conditioner Stripper Neutralizer and Floor Conditioner

Removes alkaline stripper residue from floors before recoating. Effectively dissolves ice-melt salt compounds, lime deposits and hard water stains from floors, glass, tile, and metals. Excellent for rinsing floor pads and mop heads to neutralize excess alkalinity and odors.

Micro Shield Extended-Wear Floor Sealer/Finish

A hard, durable, yet responsive floor finish which produces a brilliant gloss on resilient tile floors, marble, terrazzo, concrete, sealed wood and cork. Designed for use with floor machines from 175 to 3000 RPM. Will not powder, peel or chip. Excellent for supermarkets, department stores, hospitals, schools, industrial facilities, contractors and other high-traffic areas.

Ultra-Clean All-Purpose Cleaner

A concentrated all-purpose cleaner for use on all surfaces not harmed by water. Quickly removes dirt and grease while leaving the surface film free. For use on floors, walls, concrete, plastic, terrazzo and painted surfaces of all industrial and institutional facilities. Excellent for use as a floor finish maintainer.

Reflex Spray Buff/Restorer

This new, total-maintenance formula provides a mirror-like image on all floors coated with thermal plastic, metal interlock or polymer finishes. Excellent for recoating, rejuvenating and spray buffing. For use with 300 rpm or high-speed machines.

Rebound Cleaning & Polishing Compound

A revolutionary new floor-maintenance product designed to clean and polish floors in one labor-saving step. Simply dry-sweep the floor, apply a 3 to 4 inch stream of product and immediately high-speed burnish to a clean, bright gloss. Extends the life of floor finish which lengthens the interval where recoating or stripping becomes necessary. Packaged 12 x 1-pint bottles per carton (3 individual 4 x 1-pint cases in overpack carton).

Rejuvenator Cleaner/Maintainer

Using this cleaner/maintainer as a regular part of propane and other high-speed floor maintenance programs will greatly reduce labor and provide outstanding results. Use this one-step product as a cleaner and restorer. Mop on or use through an automatic scrubber, and follow by burnishing with high-speed machine.



Distinctive, colored packaging allows for easier job-site product identification.

The Procedure...

Floor Stripping Procedure

- 1 Before attempting any cleaning task, wear all appropriate protective clothing.
- 2 Remove or lift all furniture from floor surface. Dry-sweep or dust-mop the floor to remove dirt and debris.
- 3 Following label directions, prepare a solution of **Breakaway Mop/Strip Finish Reliquifier** in bucket with cool water. Agitate solution with a mop to mix thoroughly.
- 4 Spread a liberal solution over 15-20 running feet of the floor area to be stripped. Allow solution to emulsify old wax or finish for 3-5 minutes. Keep floor wet by adding additional stripper solution if needed.
Do not allow stripper to dry on floor!
- 5 If necessary, agitate the solution on the floor with floor machine and nylon stripping pad. Removing heavy wax or finish buildup may require the use of a "foot pad", floor scraper or grit brush.
- 6 Pick up solution with a wet-vac or auto-scrubber if available. If not, mop up emulsified finish with a second mop and rinse it in a second bucket half-filled with warm or hot water.
- 7 Repeat instructions for Steps 4-6 until the entire floor is stripped.
- 8 To eliminate all alkaline stripper residues, rinse floor thoroughly with a solution of **Neutralizer & Conditioner** and clean water. Allow to dry completely before applying finish.

Initial Application of Finish

- 1 Pour **Micro Shield Sealer/Finish** into a plastic-lined bucket. The amount of finish needed depends upon the area to be covered. Never pour unused finish from mop bucket back into container.
- 2 Dip mop into bucket so that the liquid covers only the bottom half of the mop's surface. Wring out excess finish in the wringer section of the bucket.
- 3 Working parallel to the edges of the floor apply a thin, even coat of finish. Re-immerses mop head in finish, and wring out excess. Keeping the mop in a flat position, apply finish over the rest of floor.
- 4 For optimum appearance and wear repeat procedure applying a minimum of 4 or more coats of **Micro Shield**. Allow only the first 2 coats to go to the edge.
- 5 Always apply thin coats of floor finish. Allow at least 30 minutes for finish to dry before applying the next coat. Excessive humidity or poor ventilation may increase the drying time beyond 30 minutes.

Daily Maintenance

A thorough maintenance program is essential to preserving a clean, high-gloss floor while minimizing the need for frequent strippings.

- 1 Have adequate entrance matting and vacuum daily.
- 2 Sweep or dust-mop floor to remove dirt and debris.
- 3 Following label directions for **light soil**, damp-mop and/or light-scrub the floor with an auto-scrubber using **Ultra-Clean All-Purpose Cleaner**.

Monthly Maintenance

- 1 Sweep or dust-mop floor to remove dirt and debris.
- 2 Following label directions **moderate soil**, top scrub the floor with **Ultra-Clean** using a floor machine or auto-scrubber and a green or red nylon scrubbing pad.
- 3 Apply 1 or more coats of **Micro Shield** using a clean mop. Allow 30 minutes drying time between coats. Recoat keeping 6-12 inches from edges.

Spray Buffing/Restoring

As an alternate procedure to remove black-heel-marks and renew floor finish lustre use **Reflex Spray Buff/Restorer**.

- 1 Mop floors with a solution of **Ultra-Clean**. **Never spray-buff or burnish a dirty floor!**
- 2 Following label directions, apply a light mist of **Reflex** onto floor in front of floor machine and buff with polishing pads to achieve a "wet-look" gloss.
- 3 For high-speed machines: Following label directions, apply a light to medium coat of **Reflex**. Mop on evenly across floor. Allow to dry. Burnish in normal manner.
- 4 As buffing or burnishing pad becomes dirty, reverse or replace.

Alternate Products: Rebound or Rejuvenator

